



King Home & Garden Inc. 577 Industrial Drive Fort Erie, Ontario, Canada L2A 5M4

Tel: 905-871-4766

1 Of 4

Abbreviations used on this Safety Data Sheet:

N/av. = Not available, N/ap. = Not applicable, ppm = parts per million, TLV = Threshold Limit Value. NFPA Hazard Rating: 4-Extreme, 3-High, 2-Moderate, 1-Slight, 0-None, X-Blank

SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER					
PRODUCT NAME: King Eco-Way	Crawling Insect Killer Dust®		4 - extreme		
		/ 0 >	3 - high		
OTHER NAMES:	Diatomaceous Earth	$\langle 1 \rangle \langle 1 \rangle$	2 - moderate		
	Amorphous Silica		1 - slight		
MATERIAL USE:	Insecticide Dust		0 - insignificant		
MANUFACTURER'S NAME:	King Home & Garden Inc.	NFPA HAZARD RATING	; :		
STREET ADDRESS:	577 Industrial Drive	Health - 1, Flammability - 0, Reactivity - 1			
CITY/PROVINCE:	Fort Erie, Ontario				
POSTAL CODE:	L2A 5M4				
EMERGENCY TELEPHONE NUMBER:	613-996-6666				

SECTION 2- HAZARD IDENTIFICATION

SUMMARY: Prolonged and repeated exposure to excessive concentrations of this product's dust containing respirable size ($\leq 10 \,\mu$) quartz, or any nuisance dust, can cause chronic pulmonary disease. Dust contact with eyes may cause temporary scratchiness or redness. Long term exposure can cause silicosis. The NTP (National Toxicology Program) and IARC (International Agency for Research on Cancer) has determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. A single exposure under normal conditions of use will not result in serious adverse effects.





MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED: Pre-existing upper respiratory and lung disease, such as, but not limited to: Bronchitis, emphysema, and asthma.

TARGET ORGAN(S): Lungs, Eyes

See SECTION X1 - TOXICOLOGICAL INFORMATION

SECTION 3 - COMPOSITION OF SUBSTANCE						
HAZARDOUS INGREDIENTS	%	CAS NUMBER	OSHA PEL	LD50/ /LC 50		
			(ACGIH TLV)	SPECIES AND ROUTE		
Naturally Occurring Diatomaceous Earth (Typical Analysis = 80% Silicon Dioxide)	60-100	61790-53-2	See Section VIII	N/av.		
Free Crystalline Silica or Silica, quartz	0.1 - 1	14808-60-7	See Section VIII	N/av.		
(Occurs naturally in Diatomaceous Earth) Talc 50/90	0-12	14807-96-6	See Section VIII	N/av.		
T		NICON A DE LIME A LEE	OCH A	1. 170.142		

For sampling silica dusts refer to NIOSH Analytical Method 7500 or OSHA method ID 142

SECTION 4 - FIRST AID MEASURES

Inhalation: Remove victim to fresh air. If breathing has stopped, a trained person should perform artificial respiration. Acute inhalation

can cause dryness of the nasal passage and congestion of the upper respiratory tract.

Ingestion: Do not induce vomiting. Short-term exposure not considered harmful. Drink generous amounts of water to reduce bulk and

drying effects.

Eves: Wash with large quantities of water. Consult physician if irritation persists. May cause irritation/inflammation.

Skin: May cause dryness. Remove contaminated clothing. Wash with soap and water until clean. Use moisture renewing lotions

if dryness persists. Product is not absorbed through or by the skin.



King Home & Garden Inc. 577 Industrial Drive Fort Erie, Ontario, Canada L2A 5M4

SAFETY DATA SHEET

2 Of 4

Tel·	905-871-4766	
101.	JUJ-0/1-T/00	

SECTION 5 - FIREFIGHTING MEASURES				
Flammability	No			
Means of Extinction	N/ap.	Upper Flammability Limit (% by Volume)	N/ap.	
Flashpoint (Method)	Non Flammable	Lower Flammability Limit (% by Volume)	N/ap.	
Auto ignition temperature	N/ap.	Extinguishing Media	N/ap.	
Hazardous Combustion Products	N/ap.	Special Procedures	N/ap.	
Explosion Data				
Sensitivity to Impact	No	Sensitivity to Static Discharge	No	

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PROCEDURE FOR SPILLS / LEAKS:

Avoid creating further dust. Vacuum with equipment fitted with a filter. Alternatively, wet sweep or wash away. Dispose of in accordance with local, State, and Federal Regulations.

SECTION 7 - HANDLING AND STORAGE

HANDLING PROCEDURES

Avoid creating dust. Repair or properly dispose of broken bags. Use wet process or enclosed handling.

STORAGE REQUIREMENTS

Store in a dry place to maintain. Keep containers closed and in good condition. Repair damaged containers.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION					
PERMISSABLE EXPOSURE LIMITS:	OSHA PEL	ACGIH	OHS	OHS STEL	
(for airborne, nuisance dusts) 8 hr TWA TLV 8 hr TWA					
Diatomaceous earth					
Total dust	15 mg/m^3	Not detected	4 mg/m^3	n/a	
Respirable dust	5 mg/m^3	Not detected	1.5 mg/m^3	n/a	
Crystalline quartz (respirable)	0.1 mg/m^3	0.025mg/m^3	0.025mg/m^3	n/a	

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT. Exposure to quantities of crystalline silica respirable dust (\leq 10 μ), in the forms of quartz, cristobalite or tridymite, may occur when in the presence of airborne dust. If the dust concentration levels are in excess of the OSHA Permissible Limit (PEL-TWA 8hrs) of 0.1mg/m³ or the ACGIH Threshold Limit Value (TLV) of 0.025mg/m³, the crystalline silica present is a known cause of silicosis, a progressive, sometimes fatal, lung disease. From the International Agency for Research on Cancer (IARC), a 2012 review of "Silica Dust, Crystalline, in the form of Quartz or Cristobalite" coded Monograph 100C concluded that Crystalline Silica in the form of quartz or cristobalite dust is carcinogenic to humans (Group 1).

ENGINEERING CONTROLS (SPECIFY, E.G. VENTILATION, ENCLOSED PROCESS)

Control within recommended TLV/PEL, mechanical filtration to minimize dust. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.

PERSONAL PROTECTIVE EQUIPMENT	
GLOVES	Not needed under normal conditions of use.
EYE	Use protective goggles in high dust conditions.
FOOTWEAR	As required on jobsite.
CLOTHING	Wear coveralls in high dust conditions.
RESPIRATOR	Avoid breathing dust. See instructions below

Bureau of Mines or NIOSH approved respirators for protection against pneumoconiosis producing dusts recommended when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use quarter or half mask respirator (N95) with replacement dust filter or single use dust respirator with valve. If dust concentration is greater than ten (10) times and less than one hundred (100) times the PEL use full faceplate respirator with replaceable dust filter (N95 filter); if greater than one hundred (100) and less than two hundred (200) times the PEL use power air purifying (positive pressure) respirator with replaceable filter (N95 filters); if greater than two hundred (200) times the PEL use type C, automatic-air respirator, continuous flow type (positive pressure), with full facepiece, head or helmet.



3 Of 4



King Home & Garden Inc. 577 Industrial Drive Fort Erie, Ontario, Canada L2A 5M4

Tel: 905-871-4766

SECTION 9	- PHYSICAL AND CH	EMICAL P	ROPERTIES	
PHYSICAL STATE	solid ODOR	AND APPI	EARANCE	No odor, Buff tan powder
VAPOR PRESSURE (mm Hg)	N/ap. DENSI	TY (20 deg	rees Celsius)	35lb\cu. ft. +/- 5
VAPOR DENSITY (Air = 1)	N/ap. SOLU I	BILITY IN	WATER	Insoluble, forms
SPECIFIC GRAVITY (Water=1)	2.1			colloidal suspension
FREEZING POINT	N/ap. pH			5.5 - 6.5
BOILING POINT	N/ap. EVAPO	ORATION	RATE	N/ap.
SEC	TION 10 - STABILITY A	AND REAC	TIVITY	
CHEMICAL STABILITY (IF NO, UNDER WH	ICH CONDITIONS)	YES	X	
		NO		
INCOMPATIBILITY WITH OTHER SUBSTA	NCES	YES	X	Hydrofluoric acid - silica may
(IF YES, SPECIFY)		NO		react violently
REACTIVITY, AND UNDER WHAT CONDIT	IONS	N/ap.		
HAZARDOUS DECOMPOSITION PRODUCTS	S	N/ap.		
CONDITIONS TO AVOID		None i	n Designed Use	

SECTION 11 - TOXICOLOGICAL INFORMATION

PRIMARY ENTRY ROUTE(S):

Eyes: May cause temporary irritation or inflammation.

Skin: May cause dryness with continued exposure.

Ingestion: Not considered harmful, by mouth, throat, and/or stomach. Minor irritation may occur.

Inhalation: Persistent dry cough, throat irritation and labored breathing on exertion are symptomatic of exposure to airborne dust.

Exposure may aggravate existing upper respiratory tract diseases such as asthma, bronchitis or emphysema. Acute (short term) exposure to dust levels exceeding the PEL may cause irritation of respiratory tract resulting in a dry cough. Eyes may develop redness and become itchy. Chronic (long term) exposure to crystalline silica contained by airborne diatomaceous earth, where levels are higher than TLV's, may lead to the development of silicosis, other respiratory problems, or some forms of cancer. From the International Agency for Research on Cancer (IARC), in a 2012 review of SILICA DUST, CRYSTALLINE, IN THE FORM OF QUARTZ OR CRISTOBALITE (monograph 100C) concluded that "Crystalline Silica in the form of quartz or cristobalite dust is carcinogenic to humans (group 1)." The NTP (National Toxicology Program has determined that

"Respirable crystalline silica, primarily quartz dust occurring in industrial and occupational settings, is know to be a human

carcinogen."

SECTION 12 - ECOLOGICAL INFORMATION

Product is generally considered chemically inert in the environment. Used product that has become contaminated may have significantly different characteristics than uncontaminated product, and should be re-evaluated accordingly. Dispose of in accordance with Local, State, and Federal regulations.

SECTION 13 - DISPOSAL CONSIDERATIONS

Uncontaminated waste is not hazardous as defined by the Resource Conservation and Recovery Act (RCRA, 40 CFR261). Contaminated waste must be evaluated based on contamination source. Consult local agencies as needed. Dispose of in accordance with Local, State, and Federal regulations.

SECTION 14 - TRANSPORTATION INFORMATION					
DOT Shipping Name: Not Regulated	d by DOT	Canada TDG: Not Regulate	Canada TDG: Not Regulated by TDG		
DOT Hazard Class:	n/a	Hazard Class:	n/a		
Identification #:	n/a	UN #:	n/a		



4 Of 4

Tel: 905-871-4766

L2A 5M4

	SECTION 15 - REGULATORY INFORMATION					
OSHA:	This material is considered hazardous. See section 11.	WHMIS:	Uncontrolled product according to criteria	WHMIS classification		
EINECS:	Not Listed	CND DSL:	This product is listed on the DSL			
TSCA:	This material is listed in the TSCA inventory and is not otherwise regulated by TSCA sec 4,5,6,7, or 12	NTP:	NTP: "Respirable crystalline silica, primarily quartz dust occurring in industrial and occupational settings, is known to be a human carcinogen."			
Calif Prop 65:	Listed: Crystalline Silica (airborne particles of respirable size)	RCRA: This material is not defined as hazardous waste				
	SECTION 16 - OT	HER INFO	RMATION			
PREPARED B	Y: Technical Dept		PHONE NUMBER 519-821-1282	DATE June/2021		

All information presented herein is believed to be accurate; however, it is the user's responsibility to determine in advance of need that the information is current and suitable for their circumstances. No warranty or guarantee, expressed or implied is made by King Home & Garden Inc..as to the information, or as to the safety, toxicity or the effect of this product.